Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Original) A gyro sensor characterized by comprising:

a magnetostrictive member made of a magnetostrictive element;

a drive coil for vibrating the magnetostrictive member by controlling the intensity of a magnetic field applied to the magnetostrictive member; and

detecting means for detecting changes in magnetic permeability or remnant magnetization of the magnetostrictive member, wherein changes in angular speed around a rotation axis that is orthogonal to a direction in which the magnetostrictive member vibrates are detected as changes in magnetic permeability or remnant magnetization of the magnetostrictive member caused by deformation thereof, which is brought about by the Coriolis force.

- (Original) The gyro sensor according to claim 1, wherein
 the drive coil vibrates the magnetostrictive member at a resonant frequency.
- 3. (Currently Amended) The gyro sensor according to claim 1-or-2, wherein: the detecting means includes a magnetic resistance element; and

the changes in magnetic permeability or remnant magnetization are detected as changes in electromotive force of the magnetic resistance element.

4. (Currently Amended) The gyro sensor according to claim 1-or 2, wherein;

the detecting means includes a detection coil surrounding the magnetostrictive member; and

the changes in magnetic permeability or remnant magnetization are detected as changes in inductance of the detection coil.

5. (Currently Amended) The gyro sensor according to any one of claims 1 to 4claim 1, wherein:

a magnetic biasing magnet is tightly attached to one side of the magnetostrictive member; and

a soft magnetic member around which the drive coil is disposed is tightly attached to an opposite side of the magnetostrictive member.

6. (Currently Amended) The gyro sensor according to any one of claims 1 to 5claim 1, wherein

the magnetostrictive member is a giant magnetostrictive member made of a giant magnetostrictive element.

7. (New) The gyro sensor according to claim 2, wherein:

the detecting means includes a magnetic resistance element; and

the changes in magnetic permeability or remnant magnetization are detected as changes in electromotive force of the magnetic resistance element.

8. (New) The gyro sensor according to claim 2, wherein;

the detecting means includes a detection coil surrounding the magnetostrictive member; and

the changes in magnetic permeability or remnant magnetization are detected as changes in inductance of the detection coil.

9. (New) The gyro sensor according to claim 2, wherein:

a magnetic biasing magnet is tightly attached to one side of the magnetostrictive member; and

a soft magnetic member around which the drive coil is disposed is tightly attached to an opposite side of the magnetostrictive member.

10. (New) The gyro sensor according to claim 3, wherein:

a magnetic biasing magnet is tightly attached to one side of the magnetostrictive member; and

a soft magnetic member around which the drive coil is disposed is tightly attached to an opposite side of the magnetostrictive member.

11. (New) The gyro sensor according to claim 4, wherein:

a magnetic biasing magnet is tightly attached to one side of the magnetostrictive member; and

a soft magnetic member around which the drive coil is disposed is tightly attached to an opposite side of the magnetostrictive member.

12. (New) The gyro sensor according to claim 2, wherein

the magnetostrictive member is a giant magnetostrictive member made of a giant magnetostrictive element.

13. (New) The gyro sensor according to claim 3, wherein

the magnetostrictive member is a giant magnetostrictive member made of a giant magnetostrictive element.

14. (New) The gyro sensor according to claim 5, wherein

the magnetostrictive member is a giant magnetostrictive member made of a giant magnetostrictive element.

15. (New) The gyro sensor according to claim 7, wherein

the magnetostrictive member is a giant magnetostrictive member made of a giant magnetostrictive element.